

2024.V03.2

## Midea MHELIOS Home Energy Storage Unit (5-40 kWh)

H1- (5-40) -EO



### Safe and reliable

- Highest safety standards VDE 2510-50, Lithium Iron Phosphate (LFP) Cell



### More usable energy

- 6000 cycles battery, 100% DOD



### Weather resistant

- IP 65 design, Intelligent self-heating function to resist extreme cold weather



### Quick installation

- Plug and play wiring terminals for time-saving and flexible installation

General Specification				
Dimension (W*H*D)	690x815x168mm	690x1223x168mm	690x1631x168mm	690x2038x168mm
Weight (Floor stand toolkit included)	78 kg	131 kg	184 kg	237 kg
Power module dimension (W*H*D)	690x407x168 mm			
Power module weight	25.3 kg			
Battery module dimension (W*H*D)	690x402x168 mm			
Battery module weight	53 kg			
Installation	Floor stand			
Operating temperature	-20 ~ + 55 (-4°F~131°F)			
Max. operating altitude	2000 m			
Environment	Outdoor/Indoor			
Relative humidity	5%~95%			
Cooling	Natural convection			
Protection rating	IP65			
Cell technology	Lithium-iron phosphate (LiFePO <sub>4</sub> )			
Compatible inverters	Midea Energy Manager(Three Phase)			
Certification	IEC/EN 62109-1, IEC/EN 62477, EN 61000-6-1, EN 61000-6-3, IEC62619, UN38.3, IEC/EN 62040-1, VDE 2510-50			
Warranty				
Warranty	10 jaar of 6000 cycli			

1. Test conditions: 100% depth of discharge(DoD), 0.2C rate charge & discharge at 25 C, at the beginning of life.  
 \*All specifications are subject to change without notice.